

Stick




Recessed LED spotlight (9W) with Bridgelux light source, delivering 994 lm output, CRI >90, and selectable beam angles (24° / 36°) for precise architectural lighting.

PRODUCT MATERIAL	Die-cast Aluminium
LIGHT SOURCE	Bridgelux V8 Array
MODULE LIFETIME	Approx. 50.000 hours
STANDARD DRIVER	Excluding driver, SELECT OPTION
COLORS	<ul style="list-style-type: none"> ● 35 = RAL 9003 white + RAL 9005 black ● 5 = RAL 9005 black
BEAM ANGLE	<ul style="list-style-type: none"> ▲ 24°
ADJUSTABLE	Yes - 0-20° - 360°
SIZE	Ø92 X 55mm



OPTIONS

OPTIONAL BEAM ANGLE	▲ 36° Art. no.: 4912.010.36.0
ANTI-GLARE RING	Black Included
	White Art. no.: 4912.922.99.3
	Gold Art. no.: 4912.922.99.9
GLASS	Prismatic Art. no.: 4912.933.94.0
	Frosted Art. no.: 4912.933.90.0
	Striped Art. no.: 4912.933.96.0
HONEYCOMB	Art. no.: 4912.933.91.0
DRIVER OPTIONS	On/off 500mA 6-10W Art. no.: 0110.500.10.0
	Phase cut 500mA 5-10W Art. no.: 0110.500.20.7
	DALI 500mA 4-18W Art. no.: 0118.500.40.0
	Max. 2 fixtures connected in serie per driver
POWER CABLE OPTIONS Connected to driver/fixture	Europlug 2000mm 2 X 0,75 Art. no.: 0502.075.20.0
	Wieland GST 18/3 male 2000mm 3 X 0,75 Art. no.: 0501.183.20.0
	Wieland T connector GST 18/3 200mm 3 X 0,75 Art. no.: 0500.183.20.0



ANTI-GLARE RING



GLASS



HONEYCOMB



INFORMATION

Always select a driver option and add the selected driver to your order.

▲ Full warranty only applies when fixture is purchased in combination with recommended driver.

ARTICLE NUMBER	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI	TC LIFETIME	mA
4917.500.24.Δ	V8 Array	Bridgelux	938lm	9W	104lm/W	2700K	>90	50.000 Hrs	500mA

Disclaimer

Alle technische gegevens, evenals gewichts- en afmetingsspecificaties, zijn gebaseerd op standaardwaarden. Wij behouden ons het recht om technische wijzigingen aan te brengen. Productafbeeldingen dienen ter illustratie en kunnen afwijken van het origineel.

FL

www.formaluna.be